

Avalure™ AC 120 Polymer Toxicology Studies

The toxicology studies summarized below were performed on polymers with chemical compositions representative of the Avalure™ AC 120 polymer. Therefore, the toxicology data below is expected to be predictive of the toxicity of the commercial grades of Avalure AC 120 polymer.

Skin Irritation

The skin irritation potential of the test material was evaluated undiluted in rabbits according to international OECD Guidelines No. 404, 1992; Method B4 of Commission Directive 92/69/EEC. The test material (0.5g of dry polymer, moistened with 0.5 ml distilled water) was applied to the intact skin on each of three animal backs. The dose was held in contact with the skin under a semi-occlusive binder for an exposure period of four hours. Following the exposure period, the binder was removed, and the remaining test article was wiped from the skin using tap water and paper towels. The test sites were subsequently examined and scored for dermal irritation at one, 24, 48, and 72 hours following patch removal.

Under the test conditions, the test material caused no skin irritation (Primary Irritation Index 0.0) or corrosive effects.

Eye Irritation

The eye irritation potential of the test material was evaluated undiluted according to international OECD Guidelines No. 405, 1987; Method B5 of Commission Directive 92/69/EEC. A standard amount of the test material (0.1 ml) was administered to groups of three albino rabbits. The respective test material was instilled into the conjunctival sac of one eye of the test animals while the other eye served as a control. The eyes were not washed after instillation.

Under the test conditions, the test material (undiluted) produced minimal conjunctival irritation (maximum mean score 4.0 out of 110; class 3 on a 1 to 8 scale) which cleared by 24 hours.

Skin Sensitization

The skin sensitization potential of the test material was evaluated in the guinea pig (20 test animals and 10 controls) using the Magnusson and Kligman test according to OECD Guidelines No. 406, 1992; Method B6 of Commission Directive 92/69/EEC. Based on dose rangefinding tests animals were shaved and injected intradermally with Freund's Complete Adjuvant (1:1 in distilled water), a 25 % w/v solution of the test material in distilled water, and a 25% emulsion of the test material in the Freund's solution. The sites were evaluated at 24 and 48 hours after exposure and were treated with a topical application of an undiluted solution of the test material on day 7 and covered with an occlusive dressing. The dressing was kept in place for 48 hours and then was removed. The site was evaluated 24 hours later. Following the induction phase the animals were shaved again and challenged with undiluted test material and 75% w/v in distilled water and covered again with an occlusive dressing. The dressings and test material were removed after 24 hours. The skin was again clipped and the site was read at 24 and 48 hours. At the 24 hour reading very slight erythema was noted in control and test animals given undiluted material while observations at the 48 hour reading were limited to desquamation in one test animal that received the undiluted material. Because of the irritation response, it was not possible to determine the incidence of sensitization in this group. However, no signs of erythema or edema were noted following the challenge with the 75% solution. The test material at the maximum non-irritant concentration produced a 0% (0/20) sensitization rate and was classified as a non-sensitizer to guinea pig skin.

Lubrizon Advanced Materials, Inc. / 9911 Brecksville Road, Cleveland, Ohio 44141-3247 / TEL: 800.379.5389 or 216.447.5000

The information contained herein is being furnished for informational purposes only, upon the express condition that the User makes its own assessment of the appropriate use of such information. While the information contained herein is believed to be reliable, no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for a particular application or the results to be obtained herefrom. Lubrizon Advanced Materials, Inc. ("Lubrizon") cannot guarantee how any products associated with this information will perform in

combination with other substances or in the User's process. Due to variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the information or products for the applications disclosed. Lubrizon shall not be liable and the User assumes all risk and responsibility for any use or handling of any material beyond Lubrizon's direct control. LUBRIZOL MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO,

THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. It is the User's sole responsibility to determine if there are any issues relating to patent infringement of any component or combination of components relating to the supplied information. **Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.**

For further information, please visit: www.lubrizon.com/personalcare