

ThreadFit® Thread Cutting Oil for Sprinkler Pipe



Description

ThreadFit Thread Cutting Oil for Sprinkler Pipe is an excellent heavy duty, dark colored cutting oil for all types of ferrous metal. It's special combination of anti-wear and anti-weld additives provides all the necessary lubricity and cooling modern pipe threading operations require. This balanced combination of additives will help improve die life and thread quality over other cutting oils. ThreadFit is also FGG/BM System Compatible and will not harm fittings or pipe made with CPVC resin.

For questions:
1 800 344-1822
1 800 344-3775 fax
<http://www.fppi.com>
info@fppi.com

©2001-2006 Fire Protection Products, Inc.

Directions

ThreadFit can be used in automatic and hand held applicators. Fill oil reservoir according to equipment manufacturers specifications. Mixing of different types of threading oils is not recommended. Change oil regularly for optimum performance. Dispose of used oil in accordance with all local, State and Federal ordinances and regulations. Consult Material Safety Data Sheets for additional safety and handling information.

This product is registered with CHEMTREC, a 24-hour emergency hotline. They may be reached at 1 800 424-9300.



Product Information

Health Precautions

Contains petroleum oil. Avoid breathing mists or vapors. Avoid eye contact and prolonged or repeated contact with skin. Wear safety glasses or goggles. Use good personal hygiene.

First Aid

Skin contact: wash thoroughly with soap and water. Eye contact: flush eyes with water for at least 15 minutes and seek medical attention. Ingestion: consult a physician immediately. Inhalation: move affected person(s) to fresh air and seek medical attention.

Spill or Leak

Soak up with an oil absorbent compound. Follow all state, local, Federal regulations for disposal. Don't pollute. Conserve our resources-Please recycle this container.