

**Carboset® CR-7185E**

APEO-Free, readily coalesced DIY & OEM coatings

Carboset® CR-7185E is an APEO-free acrylic copolymer emulsion designed for air or forced dry coatings on wood, metal and plastic substrates. Carboset CR-7185E resin can be formulated into clear or pigmented finishes suitable for both DIY and industrial (OEM) coatings. Carboset CR-7185E resin is readily coalesced with both ethylene and propylene glycol ethers. This polymer can be readily formulated into brush, roll, spray, dip or flow coatings. Carboset CR-7185E resin has excellent gasoline and solvent resistance, making it suitable for automotive ancillary and general industrial finishes. This hydrocarbon resistance coupled with fast dry and low MVTR (Moisture Vapor Transmission Rate) make Carboset CR-7185E resin an excellent choice for concrete curing membranes and sealers. Carboset CR-7185E resin can be blended with Sancure® 1514 dispersion, waterborne aromatic polyurethane, for additional toughness and wear resistance, when formulated for clear wood finishes for trim and flooring. Typical applications: Clear wood floor finishes | clear concrete sealers | Concrete curing membranes | General industrial finishes | Automotive metal & plastic finishes | Business machine coatings | Implement enamels

**FEATURES AND BENEFITS**

- Abrasion Resistance
- Adhesion
- Alkali Resistance
- Block Resistance
- Chemical Resistance
- Corrosion Resistance
- Dirt Pick-Up Resistance
- Durable
- Fast Drying
- Glossy
- Hardness
- Humidity Resistance
- Low MVTR
- Scratch Resistance
- Solvent Resistance
- Stain Resistance
- Water Resistance

**CHARACTERISTICS**

Characteristic Name	Value
% Weight Solids	41.0 - 43.0
Appearance	Milky White Dispersion
Brookfield Viscosity (cps)	5 - 100
Freeze/Thaw Stability	Protect from Freezing
MFFT (°C)	40
pH Value	8.0 - 8.7

## REGULATORY

- APEO-Free<sup>1</sup>

<sup>1</sup>Not intentionally added to the composition of this product

## APPLICATIONS

- Building & Construction Coatings
- Industrial OEM Coatings
- Protective Coatings
- Transportation Coatings

## AVAILABLE REGIONS

- Asia Pacific
- EMEA
- Latin America
- North America

## RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 365 days. See SDS for storage conditions and handling instructions.

## REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at [www.lubrizol.com/coatings](http://www.lubrizol.com/coatings).

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: [AmerLZAMCustomerAssistance@Lubrizol.com](mailto:AmerLZAMCustomerAssistance@Lubrizol.com) | Europe: [EMEAICustomerAssistance@Lubrizol.com](mailto:EMEAICustomerAssistance@Lubrizol.com) |

Asia: [APCustomerAssistance@Lubrizol.com](mailto:APCustomerAssistance@Lubrizol.com) | Brazil: [BrazilQualityLZAM@Lubrizol.com](mailto:BrazilQualityLZAM@Lubrizol.com)

## DISCLAIMER

Lubrizol Advanced Materials, Inc. ("Lubrizol") hopes that you have found the information provided helpful, but you are cautioned that this material, including any prototype formulas, is for informational purposes only and you are solely responsible for making your own assessment of appropriate use of the information. **TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, LUBRIZOL MAKES NO REPRESENTATIONS, GUARANTEES, OR WARRANTIES (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR REGARDING THE COMPLETENESS, ACCURACY, OR TIMELINESS OF ANY INFORMATION.** Lubrizol does not guarantee how the materials referenced herein will perform in combination with other substances, in any methods, conditions, or processes, with any equipment, or in non-laboratory environments. **BEFORE COMMERCIALIZATION OF ANY PRODUCT CONTAINING THESE MATERIALS, YOU SHOULD**

**THOROUGHLY TEST SUCH PRODUCT, INCLUDING HOW THE PRODUCT IS PACKAGED, TO DETERMINE ITS PERFORMANCE, EFFICACY, AND SAFETY.** You are solely responsible for the performance, efficacy, and safety of any products you manufacture. Lubrizol shall not be liable, and you shall assume all risk and responsibility for, any use or handling of any material. Any claims may not be approved in all jurisdictions. Any entity making claims related to these products is responsible for complying with local laws and regulations. Nothing contained herein is to be considered as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner, and it is your sole responsibility to determine if any issues related to patent infringement of any component or combination of components relating to the information provided exists. You acknowledge and agree that you are using the information provided herein at your own risk. If you are dissatisfied with the information provided by Lubrizol, your exclusive remedy shall be to not use the information.

## COPYRIGHTS

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2022, All Rights Reserved.