

PERFORMANCE COATINGS

Solsperse[™] P820

A 100% active polymeric dispersant

Solsperse™ P820 is a 100% active polymeric dispersant which will improve pigment dispersion and stability in liquid organic media.

FEATURES AND BENEFITS

- 100% Dispersant
- Color Development
- Dispersant Efficiency
- Fast Wetting
- Glossy
- High Color Strength
- High Pigment Loading
- High Solids Dispersant

CHARACTERISTICS

Characteristic Name Value Appearance Amber liquid Density (g/cc @ 1.02 15.6°C) Flash Point (°C) >200 Solsperse P820 should be thoroughly blended with the millbase resin / solvent before the addition of pigments. Incorporation Recommendations Solvent Boiling decomposes without boiling >250 Point (°C) Usage Guidelines Addition level should be based on the surface area of the pigment / filler. The dosage is typically 2 mg per square meter of pigment surface area. This is simply the BET surface area divided by 5. See Solsperse Dosage Guide for more details.

REGULATORY

• FDA

• Swiss Ordinance (Annex 10 to the Ordinance)

Published on 18 Nov, 2024

- Improved Coloristic PropertiesJetness
- Low Viscosity
- Milling Efficiency
- Particle Size Reduction
- Pigment Treatment
- Stability

APPLICATIONS

- Analog Printing Inks
- Building & Construction Coatings
- Thermoplastics

AVAILABLE REGIONS

- Asia Pacific
- EMEAI
- Latin America
- North America

RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 1,825 days. See SDS for storage conditions and handling instructions.

REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com | Asia: APCustomerAssistance@Lubrizol.com | Brazil: Brazil@ualityLZAM@Lubrizol.com

DISCLAIMER

Lubrizol Advanced Materials, Inc. ("Lubrizol") hopes that you have found the information provided helpful, but you are cautioned that this material, including any prototype formulas, is for informational purposes only and you are solely responsible for making your own assessment of appropriate use of the information. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, LUBRIZOL MAKES NO REPRESENTATIONS, GUARANTEES, OR WARRANTIES (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR REGARDING THE COMPLETENESS, ACCURACY, OR TIMELINESS OF ANY INFORMATION. Lubrizol does not guarantee how the materials referenced herein will perform in combination with other substances, in any methods, conditions, or processes, with any equipment, or in non-laboratory environments. BEFORE COMMERCIALIZATION OF ANY PRODUCT CONTAINING THESE MATERIALS, YOU SHOULD THOROUGHLY TEST SUCH PRODUCT, INCLUDING HOW THE PRODUCT IS PACKAGED, TO DETERMINE ITS PERFORMANCE, EFFICACY, AND SAFETY. You are solely responsible for the performance, efficacy, and safety of any products you manufacture. Lubrizol shall not be liable, and you shall assume all risk and responsibility for, any use or handling of any material. Any claims may not be approved in all jurisdictions. Nothing contained herein is to be considered as

Published on 18 Nov, 2024

- Particle Dispersions
- Surface Treatments

permission, recommendation, or inducement to practice any patented invention without permission of the patent owner, and it is your sole responsibility to determine if any issues related to patent infringement of any component or combination of components relating to the information provided exists. You acknowledge and agree that you are using the information provided herein at your own risk. If you are dissatisfied with the information provided by Lubrizol, your exclusive remedy shall be to not use the information.

COPYRIGHTS

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2022, All Rights Reserved.