#### **PERFORMANCE COATINGS**

### **PRODUCT DATA SHEET**

### Lanco™ LiquiMatt 5730

Liquid Matting Preparation for Solvent-Based Coatings

Lanco™ LiquiMatt 5730 is a unique combination of polyolefins and silica processed to produce a dispersion with a very tight particle size distribution. It can be used as stand-alone matting agent in wood coating formulations to provide an excellent mix of surface protection, feel and matting in a single easy-to-use product. Because it replaces the need for multiple powder surface modifiers, Lanco LiquiMatt 5730 eliminates dust and incorporation problems.

#### **FEATURES AND BENEFITS**

- · Ease of Dispersibility
- Mar Resistance
- Matting Efficiency

- Soft Feel
- Solvent Based

### **CHARACTERISTICS**

Characteristic Name	Value
Addition Levels (% on total formula)	The recommended addition level for Lanco LiquiMatt 5730 is between 2.0 and 5.0% as supplied, based on total formulation weight. For lower gloss finishes, an addition rate of up to 8% may be required
Appearance	White opaque liquid
Chemical Type	Polyolefin silica compound
Density (g/cm3 @ 20°C)	0.96
Incorporation Recommendations	Lanco LiquiMatt 5730 can be easily incorporated into the coating at the let-down or post addition stage, using low speed mixers.
Solids (wt %)	24
Solvent	Xylene/ butyl acetate

### **REGULATORY**

APEO-Free¹

NMP-Free¹

<sup>1</sup>Not intentionally added to the composition of this product

Published on 12 Sep, 2024

Lanco™ LiquiMatt 5730 Performance Coatings

## **AVAILABLE REGIONS**

- Asia Pacific
- EMEAI
- Latin America
- North America

### **RECOMMENDED STORAGE AND RE-TEST DATE**

Lubrizol recommends retesting quality after 365 days. See SDS for storage conditions and handling instructions.

#### **REGULATORY STATUS**

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAlCustomerAssistance@Lubrizol.com | Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

### **DISCLAIMER**

Lubrizol Advanced Materials, Inc. ("Lubrizol") hopes that you have found the information provided helpful, but you are cautioned that this material, including any prototype formulas, is for informational purposes only and you are solely responsible for making your own assessment of appropriate use of the information. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, LUBRIZOL MAKES NO REPRESENTATIONS, GUARANTEES, OR WARRANTIES (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR REGARDING THE COMPLETENESS, ACCURACY, OR TIMELINESS OF ANY INFORMATION. Lubrizol does not guarantee how the materials referenced herein will perform in combination with other substances, in any methods, conditions, or processes, with any equipment, or in non-laboratory environments. BEFORE COMMERCIALIZATION OF ANY PRODUCT CONTAINING THESE MATERIALS, YOU SHOULD THOROUGHLY TEST SUCH PRODUCT, INCLUDING HOW THE PRODUCT IS PACKAGED, TO DETERMINE ITS PERFORMANCE, EFFICACY, AND SAFETY. You are solely responsible for the performance, efficacy, and safety of any products you manufacture. Lubrizol shall not be liable, and you shall assume all risk and responsibility for, any use or handling of any material. Any claims may not be approved in all jurisdictions. Any entity making claims related to these products is responsible for complying with local laws and regulations. Nothing contained herein is to be considered as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner, and it is your sole responsibility to determine if any issues related to patent infringement of any component or combination of components relating to the information provided exists. You acknowledge and agree that you are using the information provided herein at your own risk. If you are dissatisfied with the information provided by Lubrizol, your exclusive remedy shall be to not use the information.

Published on 12 Sep, 2024 Page 2 of 3

Lanco™ LiquiMatt 5730 Performance Coatings

# **COPYRIGHTS**

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2022, All Rights Reserved.

Published on 12 Sep, 2024 Page 3 of 3