

SOLUTION DATA SHEET

Unique Pearlbond™ 300 Series, Soft TPU for Film & Sheet Thermobonding Adhesives



Markets	Textile lamination, footwear, leather goods, electronics and transportation and elastic seam tape.
Polymer	Pearlbond™ thermoplastic polyurethane (TPU)
Key Benefits	<ul style="list-style-type: none"> • Plasticizer-free, soft material (approx. 55-70 Shore A) • Soft touch, good haptics • Improved processability and wide wettability • Good adhesion properties at low temperatures • Rigid system modifier

The textile lamination market has always required polymers with a soft feel. Until recently, the only technology available with this characteristic was plasticized TPU. The challenge for the TPU industry was to eliminate the plasticizer while maintaining the low hardness and tack-free properties of the TPU.

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.

© 2020 The Lubrizol Corporation.
All rights reserved. All marks are the property of The Lubrizol Corporation.

 contact us at
<http://go.lubrizol.com/EP>

This challenge has been overcome by Lubrizol technology: Tin- and wax-free Pearlbond 300 series combines all the demands from the industry: A very soft, plasticizer-free material with good processability, and no residual tack.

The soft, adhesive melting temperature of Pearlbond™ 300 TPU series fills the gap between crystalline and amorphous TPU

This novel TPU range is a powerful thermobonding option for designers and manufacturers who want to convert their products into unique solutions. The advanced science of this technology, combined with recent advances in machinery and the increasing sophistication of textiles, delivers benefits such as an agreeable soft touch texture, absence of residual surface tackiness, excellent processing properties and good grip/anti-slip properties.

Pearlbond™ 300, Pearlbond 301 and Pearlbond 302 solutions provide:

- Superior soft hand feel in textiles (jackets, shirts, skirts, dresses, trousers, pullovers, shirts, beach towels, table linen, curtains, leather, synthetic leather, Kevlar, ABS, and PVC, among others)
- Good adhesion to fabrics (e.g.: cotton, acrylic, nylon, silk and polyester)
- Good wash resistance.

The latest addition is **Pearlbond 300** polymer. The portfolio available can be seen below:

	Pearlbond™ 300	Pearlbond™ 301	Pearlbond™ 302
Shore A hardness	70	55	55
Tensile Strength (MPa)	9	9	14
Elongation @ break (%)	855	1050	900
Modulus @ 100% Elongation	1.8	1.1	1.4
Activation Temperature (°C)	<80	≤100	≤110
Wash Resistance (°C)	<40	<60	<70
Unique Features	Soft touch. Very low activation temperature	Soft touch. Adapts to body movement	Low Energy stretching. Good Wash resistance


Pearlbond 300 material stands out as the lowest viscosity, soft TPU that can be processed on highly demanding equipment such as slot dies. All 3 grades offer outstanding gel-free properties which makes them ideal to convert into high-quality films via flat die and extruded blown film process.

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.

These innovative solutions can be processed across a wide temperature window. The new Pearlbond offering provides elastomeric performance together with the appropriate recovery. This results in pleasant-to-wear garments.

Typical industries and applications that can benefit from the Pearlbond™ 300 TPU series include:

- Textile lamination
- Automotive
- Footwear
- Electronics
- Outdoor equipment
- Furniture
- Synthetic leather & Leather
- Elastic seam tapes
- Heat transfer labels



For more information, please visit our web site: www.lubrizol.com/Engineered-Polymers

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.

© 2020 The Lubrizol Corporation.
All rights reserved. All marks are the property of The Lubrizol Corporation.

 contact us at
<http://go.lubrizol.com/EP>